1998/G-026 CLEAN COPY CLAIMS



- A composite article as claimed in claim 1, wherein the strength of the bond between the polyacetal and the modified styrene-olefin elastomer is at least 0.5 N/mm².
- 4. A composite article as claimed in claim 1, wherein the polyacetal used comprises a polyoxymethylene copolymer.
- 5. A composite article as claimed in claim 1, wherein the non-olefinic thermoplastic material has been selected from the class consisting of thermoplastic polyesterurethane elastomers, thermoplastic polyetherurethane elastomers. thermoplastic polyesters, thermoplastic polyesterester elastomers, thermoplastic polyetherester elastomers. thermoplastic polyetheramide elastomers. thermoplastic polyamides, thermoplastic polycarbonates, thermoplastic polyacrylates, acrylate rubbers and styrene-acrylonitrile-acrylate rubbers (ASA).
- 6. A composite article as claimed in claim 1, in the form of a molding made from polyacetal, which has been entirely or to some extent coated with the modified styrene-olefin elastomer.
- 7. A composite article as claimed in claim 1, in the form of a molding made from polyacetal, to which at least one other molding made from the modified styrene-olefin elastomer has been molded-on.
- 8. A composite article as claimed in claim 1, which has been produced by multicomponent injection molding.